



STANDARD PIPE SIZES

Materials	Outside Pipe Diameters				
	1½"	2"	3"	4"	5"
Steel	1.900	2.375	3.500	4.500	5.560
ABS/PVC Plastic (Schedule 40)	1.900	2.375	3.500	4.500	5.560
Cast Iron	1.900	2.350	3.350	4.380	5.300
Copper	1.625	2.125	3.125	4.125	5.125
Thinwall Plastic PVC (SDR 35)			3.250	4.215	
Stainless Steel		2.000	3.000	4.000	5.000
Extra Heavy Cast Iron		2.380	3.500	4.500	5.500
Duriron®	2.190	2.630	3.750	4.750	
Ductile Iron				4.800	
Asbestos Cement (Class 1500 - Transite)				4.810	
Clay				5.370	

- *Quick and easy repair of most types and sizes of Drain Waste & Vent (DWV) and Sanitary pipes*
- *No more trips to a job site with the wrong coupling*
- *Increased efficiency equals labor cost savings*
- *Accommodates significant shear load, deflection and internal hydrostatic pressure*
- *Recommended installation of 80 in/lbs. minimum torque for the 4", and 60 in/lbs. minimum torque for the 2" & 3"*
- *For non-pressure, gravity flow DWV and Sanitary applications only*

MAXADAPTOR® DWV & Sanitary Couplings

SIZE	PART NUMBER	DESCRIPTION	O.D. RANGE
2"	19300	MAX DWV 2	1.63" - 2.50"
3"	19305	MAX DWV 3	3.00" - 4.13"
4"	19310	MAX DWV 4	4.00" - 5.56"
4"+	19203	MAX 4 Oversize	4.21" - 5.90"

U.S. Patent No. US 2020/0166164 A1

Canada Patent No. CA 3058951 A1

Specifications: Exceeds the requirements of ASTM C1173-18. IAPMO 4224 listed.

Gripper Gasket LLC

1660 Leeson Lane | Corona, CA 92879

(951) 479-4999 | (951) 479-4997 Fax

maxadaptor.com